



coma I

pureWhite | pureColor

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

COMA-L- _____ - _____ - _____ - _____ - _____ - Y04
 TYP - LUMINOUS COLOR DIMMING BEAM ANGLE WIRING HOUSING COLOR

TYP - LUMINOUS COLOR	
PW22	pureWhite - 2200 K
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K
PCRE	pureColor - Red
PCGR	pureColor - Green
PCBL	pureColor - Blue
PCAM	pureColor - Amber

BEAM ANGLE	
7X7	7° x 7°
13X13	13° x 13°
30X30	30° x 30°
66X66	66° x 66°
90X114	90° x 114°
8X31	8° x 31°
11X45	11° x 45°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°

DIMMING	
NDIM	Non-dimmable
DMX	Dimmable - DMX
0-10V	Dimmable - 0-10V
IOT	Dimmable - IOT

WIRING	
CE	Europe
ETL	North America

HOUSING COLOR	
WH	White powdercoated
BL	Black powdercoated

Sample Order Code: COMA-L-PW27-DMX-66X66-CE-WH-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.