



tantulus 3 xhp indoor

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-3-XHP-IN- _____ - _____ - _____ - _____ - Y02

TYP - LUMINOUS COLOR
FIXTURE LENGTH
BEAM ANGLE
MOUNTING OPTION

TYP - LUMINOUS COLOR	
PW20	pureWhite - 2000 K
PW22	pureWhite - 2200 K
PW25	pureWhite - 2500 K
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K
PW45	pureWhite - 4500 K
PW65	pureWhite - 6500 K

BEAM ANGLE	
30X120(F)	30° x 120° frost
60X120(F)	60° x 120° frost
120X120(C)	120° x 120° clear
120X120(F)	120° x 120° frost
120X120(W)	120° x 120° white

FIXTURE LENGTH	
105	105 mm / 4.13 in (only end fitting)
207	207 mm / 8.15 in (only end fitting)
310	310 mm / 12.2 in
615	615 mm / 24.21 in
920	920 mm / 36.22 in
1225	1225 mm / 48.23 in
1530	1530 mm / 60.24 in
1835	1835 mm / 72.24 in

MOUNTING OPTION	
K0	Bracket Set 0°
K15	Bracket Set 15°
K30	Bracket Set 30°
K45	Bracket Set 45°
K60	Bracket Set 60°
KADJ	Positioning Hinge
Fixed Angle:	
Bracket count: 2 <= 1225 mm (48.23 in) > 3	
HKadj: Bracket count: 2 for all lengths	

* Project-specific options are available - Please contact our Sales Representative for further information.