


INTERSTELLAR DATA-HUB

Dimensions



Metric:
160 x 90 x 260 mm [X x Y x Z]
Imperial
6.30 x 3.55 x 10.24 in [X x Y x Z]

Technical Data

Housing	Polycarbonate
Housing Color	RAL 7001 Silver gray
Power Consumption	max. 10 W
Internal power supply	100 - 264 VAC (50 - 60 Hz)
Protection Class	I
Environment	Indoor, Outdoor
Ingress protection rating	IP66
Humidity	0 to 95%, non-condensing
Ambient temperature (Operation)	-40 °C to 40 °C | -40 °F to 104 °F
Ambient temperature (Storage)	5 °C to 40 °C | 41 °F to 104 °F
Ambient temperature (Start-up process)	-25 °C to 40 °C | -13 °F to 104 °F
Impact protection rating	IK08
Approbation	CE
Weight	1.6 kg

Designed and Developed in Bavaria.
Made in Germany.

sales@biontechnologies.com
www.biontechnologies.com

Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.

INTERSTELLAR DATA-HUB

Configurator

IDH - (1) -Y01

1 Protocol / Signal	
DMX	DMX
DALI	DALI (Comming soon)

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0

All information without guarantee. Errors, changes and misprints excepted.