

# linea xs / xc leader cable

## Dimensions

**Metric:**
1525 mm, 3050 mm, 9150 mm, 15250 mm (X)
**Imperial**
60.04 in, 120.08 in, 360.24 in, 600.40 in (X)

## Technical Data

| | |
|---|---|
| Outer cable diameter | 11 mm \| 0.44 in |
| Outer diameter connector | 30 mm \| 1.19 in |
| Minimum bending radius Cable (fixed installation) | 4x Outer Ø |
| Minimum bending radius cable (flexible) | 15x Outer Ø |
| Environment | Indoor, Outdoor |
| Ingress protection rating | IP66 |
| Ambient temperature (Operation) | -40 °C to 80 °C \| -40 °F to 176 °F |
| Approbation | ETL, CE |
| | Designed and Developed in Bavaria. Made in Germany. |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.

# linea xs / xc leader cable

## Configurator

LIN-XSXC-LEAD -(1)_____ -(2)_____-Y01

| 1 Dimension | |
|---|---|
| 1525 | 1525 mm / 60.04 in |
| 3050 | 3050 mm / 120.08 in |
| 9150 | 9150 mm / 360.24 in |
| 15250 | 15250 mm / 600.39 in |

| 2 Wiring configuration | |
|---|---|
| NDIM | NDIM / IOT |
| 0-10V | 0 - 10V |
| DMX | DMX |
| EXT | EXT |

sales@biontechnologies.com
www.biontechnologies.com
Phone:
(DE) +49 8231 95787 0



All information without guarantee. Errors, changes and misprints excepted.