



discus xl
pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

DIS-XL- _____ - _____ - _____ - _____ - _____ - Y01
 TYP - LUMINOUS COLOR DIMMING BEAM ANGLE WIRING HOUSING COLOR

TYP - LUMINOUS COLOR	
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K

DIMMING	
NDIM	Non-dimmable
0-10V	Dimmable - 0-10V
IOT	Dimmable - IOT
DALI	Dimmable - DALI
DMX	Dimmable - DMX

BEAM ANGLE	
10X10	10° x 10°
22X22	22° x 22°
34X34	34° x 34°
60X60	60° x 60°
8X31	8° x 31°
10X40	10° x 40°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°

WIRING	
CE	Europe
ETL	North America

HOUSING COLOR	
DB	DB703 powdercoated
WH	White powdercoated
BL	Black powdercoated
RAL____	Custom Color RAL

* Project-specific options are available - Please contact our Sales Representative for further information.