



linea m eco indoor

pureWhite | pureColor

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-ECO-IN- _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS COLOR	BEAM ANGLE	HOUSING COLOR	LEADERCABLE LENGTH	GLARE PROTECTION	MOUNTING OPTION
TYP - LUMINOUS COLOR		HOUSING COLOR			
PW22 pureWhite - 2200 K		AA Aluminium anodized (Standard)			
PW27 pureWhite - 2700 K		BA Black anodized			
PW30 pureWhite - 3000 K					
PW40 pureWhite - 4000 K					
	BEAM ANGLE		LEADERCABLE LENGTH		
8X8 8° x 8°			ETE End to end - wiring		
10X10 10° x 10°			003 + 30 cm (ca. 1 ft)		
23X23 23° x 23°			006 + 60 cm (ca. 2 ft)		
43X43 43° x 43°			009 + 90 cm (ca. 3 ft)		
52X52 52° x 52°			012 + 1,2 m (ca. 4 ft)		
8X31 8° x 31°				GLARE PROTECTION	
10X42 10° x 42°				OP No glare protection	
12X60 12° x 60°				HL Hex louver (internal)	
14X100 14° x 100°				LL0 Linear louver (internal)	
30X60 30° x 60°					MOUNTING OPTION
20X60Y10R 20° x 60° (Tilt in C0-plane: 10°)					MPA Mounting Plate Basic
20X60Y10L 20° x 60° (Tilt in C0-plane: -10°)					MSH Mounting Set Hinge

Sample Order Code: linea-m-eco-in-pW35-dim-DMX-3/922-8x31-AA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.