



linea xs inground eco

pureWhite | pureColor

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

linea-xs-inground-eco- _____ - _____ - _____ - _____ - _____ - Y01

TYP - LUMINOUS
COLOR

DIMMING

FIXTURE LENGTH

BEAM ANGLE

GLARE
PROTECTION

TYP - LUMINOUS COLOR	
PW22	pureWhite - 2200 K
PW27	pureWhite - 2700 K
PW30	pureWhite - 3000 K
PW35	pureWhite - 3500 K
PW40	pureWhite - 4000 K
PCRE	pureColor - Red
PCGR	pureColor - Green
PCBL	pureColor - Blue
PCAM	pureColor - Amber

FIXTURE LENGTH	
629	629 mm / 24.76 in
934	934 mm / 36.77 in
1239	1239 mm / 48.78 in

GLARE PROTECTION	
OP	No glare protection
HL	Hex louver (internal)
LL0	Linear louver (internal)

BEAM ANGLE	
8X8	8° x 8°
10X10	10° x 10°
23X23	23° x 23°
43X43	43° x 43°
8X31	8° x 31°
10X42	10° x 42°
12X60	12° x 60°
14X100	14° x 100°
30X60	30° x 60°
60X30	60° x 30°

DIMMING	
NDIM	Non-dimmable
DALI	Dimmable - DALI
0-10V	Dimmable - 0-10V
DMX	Dimmable - DMX

Sample Order Code: LIN-XS-IN-ECO

* Project-specific options are available - Please contact our Sales Representative for further information.