



tantulus outdoor

RGBW

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-OUT-- _____ - _____ - _____ - _____ - Y31

TYP - LUMINOUS COLOR		FIXTURE LENGTH		BEAM ANGLE		MOUNTING OPTION	
RGBW26	RGBW - 2600 K	210	210 mm / 8.27 in	30X120F	30° x 120° frost	MOUNTING OPTION K0 Bracket Set 0° K15 Bracket Set 15° K30 Bracket Set 30° K45 Bracket Set 45° K60 Bracket Set 60° KADJ Positioning Hinge Fixed Angle: Bracket count: 2 <= 1225 mm (48.23 in) > 3 HKadj: Bracket count: 2 for all lengths	
RGBW33	RGBW - 3300 K	310	310 mm / 12.2 in	120X120W	120° x 120° white		
RGBW40	RGBW - 4000 K	415	415 mm / 16.34 in	120X120F	120° x 120° frost		
		515	515 mm / 20.28 in				
		615	615 mm / 24.21 in				
		720	720 mm / 28.35 in				
		820	820 mm / 32.28 in				
		920	920 mm / 36.22 in				
		1025	1025 mm / 40.35 in				
		1125	1125 mm / 44.29 in				
		1225	1225 mm / 48.23 in				
		1330	1330 mm / 52.36 in				
		1430	1430 mm / 56.3 in				
		1530	1530 mm / 60.24 in				
		1635	1635 mm / 64.37 in				
		1735	1735 mm / 68.31 in				
		1835	1835 mm / 72.24 in				

* Project-specific options are available - Please contact our Sales Representative for further information.