



tellus surface hpq

RGBWquad

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-S-HPQ- _____ - _____ - _____ - _____ - _____ - _____ - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	HOUSING COLOR	GLARE PROTECTION	POSITION LEADER CABLE																																																																																
<table border="1"> <thead> <tr> <th colspan="2">TYP - LUMINOUS COLOR</th> </tr> </thead> <tbody> <tr> <td>RGBW40</td> <td>RGBW - 4000 K</td> </tr> <tr> <td>RGBW65</td> <td>RGBW - 6500 K</td> </tr> </tbody> </table>	TYP - LUMINOUS COLOR		RGBW40	RGBW - 4000 K	RGBW65	RGBW - 6500 K	<table border="1"> <thead> <tr> <th colspan="2">DIMMING</th> </tr> </thead> <tbody> <tr> <td>DMX</td> <td>Dimmable - DMX</td> </tr> <tr> <td>IOT</td> <td>Dimmable - IOT</td> </tr> </tbody> </table>	DIMMING		DMX	Dimmable - DMX	IOT	Dimmable - IOT	<table border="1"> <thead> <tr> <th colspan="2">FIXTURE LENGTH</th> </tr> </thead> <tbody> <tr> <td>352</td> <td>352 mm / 13.86 in</td> </tr> <tr> <td>657</td> <td>657 mm / 25.87 in</td> </tr> <tr> <td>962</td> <td>962 mm / 37.87 in</td> </tr> <tr> <td>1267</td> <td>1267 mm / 49.88 in</td> </tr> </tbody> </table>	FIXTURE LENGTH		352	352 mm / 13.86 in	657	657 mm / 25.87 in	962	962 mm / 37.87 in	1267	1267 mm / 49.88 in	<table border="1"> <thead> <tr> <th colspan="2">BEAM ANGLE</th> </tr> </thead> <tbody> <tr> <td>10X10</td> <td>10° x 10°</td> </tr> <tr> <td>22X22</td> <td>22° x 22°</td> </tr> <tr> <td>34X34</td> <td>34° x 34°</td> </tr> <tr> <td>60X60</td> <td>60° x 60°</td> </tr> <tr> <td>8X31</td> <td>8° x 31°</td> </tr> <tr> <td>10X40</td> <td>10° x 40°</td> </tr> <tr> <td>12X60</td> <td>12° x 60°</td> </tr> <tr> <td>14X100</td> <td>14° x 100°</td> </tr> <tr> <td>30X60</td> <td>30° x 60°</td> </tr> <tr> <td>WWW</td> <td>30° x 58° (Tilt in C0-plane: -14°)</td> </tr> <tr> <td>WWN</td> <td>30° x 11° (Tilt in C0-plane: -14°)</td> </tr> </tbody> </table>	BEAM ANGLE		10X10	10° x 10°	22X22	22° x 22°	34X34	34° x 34°	60X60	60° x 60°	8X31	8° x 31°	10X40	10° x 40°	12X60	12° x 60°	14X100	14° x 100°	30X60	30° x 60°	WWW	30° x 58° (Tilt in C0-plane: -14°)	WWN	30° x 11° (Tilt in C0-plane: -14°)	<table border="1"> <thead> <tr> <th colspan="2">WIRING</th> </tr> </thead> <tbody> <tr> <td>CE</td> <td>Europe</td> </tr> <tr> <td>ETL</td> <td>North America</td> </tr> </tbody> </table>	WIRING		CE	Europe	ETL	North America	<table border="1"> <thead> <tr> <th colspan="2">HOUSING COLOR</th> </tr> </thead> <tbody> <tr> <td>DB</td> <td>DB703 powdercoated</td> </tr> <tr> <td>WH</td> <td>White powdercoated</td> </tr> <tr> <td>BL</td> <td>Black powdercoated</td> </tr> <tr> <td>RAL____</td> <td>Custom Color RAL</td> </tr> </tbody> </table>	HOUSING COLOR		DB	DB703 powdercoated	WH	White powdercoated	BL	Black powdercoated	RAL____	Custom Color RAL	<table border="1"> <thead> <tr> <th colspan="2">GLARE PROTECTION</th> </tr> </thead> <tbody> <tr> <td>OP</td> <td>No glare protection</td> </tr> <tr> <td>HL</td> <td>Honeycomb louver</td> </tr> <tr> <td>LL00</td> <td>Linear louver 0°</td> </tr> <tr> <td>CGC</td> <td>customized glare control</td> </tr> <tr> <td colspan="2">Use LL17 only with beam angle www or wwn</td> </tr> </tbody> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn		<table border="1"> <thead> <tr> <th colspan="2">POSITION LEADER CABLE</th> </tr> </thead> <tbody> <tr> <td>ZS</td> <td>side feed</td> </tr> <tr> <td>ZR</td> <td>back feed</td> </tr> </tbody> </table>	POSITION LEADER CABLE		ZS	side feed	ZR	back feed
TYP - LUMINOUS COLOR																																																																																							
RGBW40	RGBW - 4000 K																																																																																						
RGBW65	RGBW - 6500 K																																																																																						
DIMMING																																																																																							
DMX	Dimmable - DMX																																																																																						
IOT	Dimmable - IOT																																																																																						
FIXTURE LENGTH																																																																																							
352	352 mm / 13.86 in																																																																																						
657	657 mm / 25.87 in																																																																																						
962	962 mm / 37.87 in																																																																																						
1267	1267 mm / 49.88 in																																																																																						
BEAM ANGLE																																																																																							
10X10	10° x 10°																																																																																						
22X22	22° x 22°																																																																																						
34X34	34° x 34°																																																																																						
60X60	60° x 60°																																																																																						
8X31	8° x 31°																																																																																						
10X40	10° x 40°																																																																																						
12X60	12° x 60°																																																																																						
14X100	14° x 100°																																																																																						
30X60	30° x 60°																																																																																						
WWW	30° x 58° (Tilt in C0-plane: -14°)																																																																																						
WWN	30° x 11° (Tilt in C0-plane: -14°)																																																																																						
WIRING																																																																																							
CE	Europe																																																																																						
ETL	North America																																																																																						
HOUSING COLOR																																																																																							
DB	DB703 powdercoated																																																																																						
WH	White powdercoated																																																																																						
BL	Black powdercoated																																																																																						
RAL____	Custom Color RAL																																																																																						
GLARE PROTECTION																																																																																							
OP	No glare protection																																																																																						
HL	Honeycomb louver																																																																																						
LL00	Linear louver 0°																																																																																						
CGC	customized glare control																																																																																						
Use LL17 only with beam angle www or wwn																																																																																							
POSITION LEADER CABLE																																																																																							
ZS	side feed																																																																																						
ZR	back feed																																																																																						

* Project-specific options are available - Please contact our Sales Representative for further information.